

CB-Spray

Product information



Field of application:	Test spray for identifying capsule destruction following printing or finishing processes.
Product composition:	Test spray, spray can, propellant: purified compressed air.
Product description:	Preparation of bisphenol A, acetone and a mixture of n and i cyclic hydrocarbons in the range C6-C7; low hexane and aromatic hydrocarbon content. Purified compressed air as propellant.
Dermatological and toxicological safety:	No acute toxicity. Prolonged and frequent skin contact can cause skin irritation or possibly inflammation (dermatitis) due to the strong degreasing action. Vapours irritate the airways at elevated concentrations. Dizziness, headaches and, in the case of intense exposure, unconsciousness are possible.
Environmental hazards:	Partially water-soluble. Mild toxicity for aquatic life.
Storage and handling:	Keep away from direct sunlight and other sources of heat or ignition. Store in a cool place. Observe laws and regulations on the storage and use of flammable substances. Ensure good ventilation or extraction at the workplace.
Fire hazard:	Highly flammable, R11.
Disposal:	Product: in accordance with local official regulations.
First aid measures:	General information: avoid prolonged contact, degreasing risk. a) Ingestion: Do not induce vomiting, call a doctor. b) Eye contact: Hold lid open and rinse with plenty of water, call a doctor. c) Skin contact: Immediately remove soiled clothing, rinse affected areas with plenty of water. d) Inhalation: Supply fresh air, call a doctor. In case of respiratory arrest or irregularity: mouth-to-mouth resuscitation or administration of oxygen.



Mitsubishi HiTec Paper Bielefeld GmbH
Niedernholz 23 | 33699 Bielefeld | Germany
Tel. +49 (0) 521 2091 0
Fax +49 (0) 521 2091 506
www.mitsubishi-paper.com

